



MODEL

DESCRIPTION

BG-12000
Water Filtration System

Part # WI-BG12000



Electronic flow meter, included with the BG-12000 system.

LEVEL 3 Body Glove Water Filter System.

Single Cartridge Design has **Quad-Stage filtration** and a ****0.2 Micron Pharmaceutical-Grade Membrane**. Features a recyclable cartridge with an easy recycle program, an **electronic flow meter**, and a filter change indicator.

FLOW RATE: 0.75 GPM
CAPACITY: 1,000 gallons or 1 year

Dimensions: W = 4.5" / D = 4.75" / H = 18.75"
(height includes 2.5" clearance for cartridge change purposes)

For filter faucet options, see our faucet guides
Enhance your water with an EverHot® Instant Hot System or EverCold® Water Chiller.



REDUCES: Chlorine Taste & Odor • Chloramines • **Cloudiness, Sediment, Rust
Giardia Lamblia Cysts • Cryptosporidium Parvum Cysts • *Lime Scale
Asbestos Fibers • **Oxidized Iron • **Oxidized Manganese • **Oxidized Sulfides
0.5-1.0 Micron, Nominal Particulate Reduction, Class 1 • Lead • Trihalomethanes (TTHMs)
Volatile Organic Chemicals (VOCs) • Methyl Tertiary-Butyl Ether (MTBE)
NEWLY CERTIFIED FOR 0.2 MICRON REDUCTION OF THESE PHARMACEUTICALS & EMERGING COMPOUNDS:
Phenytoin • Naproxen • Estrone • Ibuprofen • Bisphenol A • Nonyl phenol

**Based on Manufacturer's Data *Contains KDF, a lime-scale control agent



<p>System Tested and Certified by NSF International against NSF/ANSI Standards 42, 53, 401 and CSA B48 3.1 in Model BG-12000 for the reduction of:</p>	<p>Standard 53 - Health Effects</p> <ul style="list-style-type: none"> • Chemical Reduction • Lead • TTHM • VOC • MTBE • Mechanical Filtration • Cysts • Asbestos 	<p>Standard 42 - Aesthetic Effects</p> <ul style="list-style-type: none"> • Chemical Reduction • Chlorine Taste & Odor • Chloramines • Mechanical Filtration • Particulate Reduction- Class I 	<p>Standard 401 - Pharmaceuticals: Emerging Compounds / incidental contaminants</p> <ul style="list-style-type: none"> • Phenytoin • Ibuprofen • Naproxen • Bisphenol A • Estrone • Nonyl phenol
--	--	---	--

BG-12000C
Replacement Cartridge

Part # WI-BG12000C



FLOW RATE: 0.75 GPM / **CAPACITY:** 1,000 gallons or 1 year

EASY QUICK-CHANGE REPLACEMENT CARTRIDGE: Body Glove Water Filter Systems have an automatic shut-off valve built into the head unit, so changing the cartridge is a breeze. Includes a filter change indicator.



Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components - Lead Content and S.3874, Reduction of Lead in Drinking Water Act, CAAB 1953 and VT Act 193.



MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you. Problems due to excessive water pressure are NOT covered by this product's warranty. **BEFORE** installation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Dept. at 800.322.WATER(9283)

Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.