# LACAVA

## Specifications:

# ZOOM deck-mount electronic faucet EX22/EX22.5/EX22.35


Installation: Exterior Dimensions: Material:	deck- mount 1-hole, touch-free H: 5 1/2" SPOUT: 6 3/4"
	solid brass construction
Water use:	1 GPM (EX22), 0.5 GPM (EX22.5), 0.35 GPM (EX22.35)
Power supply:	AC/DC
Finishes:	CR - polished chrome
	PN - polished nickel
	NI - brushed nickel
	BG - brushed gold
	44 - matte black
	TN - titanium
	MW - matte white (made to order)
Cutout Size:	Ø 1 3/8″
Accessories included:	power adapter, flexible supply
	line F 1/2" and battery box
Features:	· ·

#### eatures:

- Power supply options:
  - AC transformer with a plug to electricity and/or
  - DC battery pack for 4 x AA alkaline batteries (batteries not included)
    - on average lasts for 108,000 use cycles
- For cold or premixed water (mixer sold separately)
- 10 seconds metering cycles •
- Sensing range: 2"-12" (5cm 30cm) adjustable with a button on the side of the control box
- Sensing distance is set during installation see manual
- Water pressure: 15-90 PSI, recommended 43.5 PSI
- Water temperature: 34-1200Fahrenheit (1-500Celsius)

## Codes + Standards:

- Meets and exceeds applicable national codes and standards
- 1 GPM Watersence certified (EX22)
- 0.5 GPM CAL-Green compliant (EX22.5)
- 0.35 GPM LEED Credit (EX22.35)



## Recommended Items:

- Replacement parts:
  - #4ABATPK replacement battery pack
  - #EX22-SENR replacement sensor
- Mixing valves (sold separately)
  - #EX20A mechanical mixing valve
  - #EX25A integrated thermostatic valve
- American size grid drains
  - #7100-18 without overflow holes
  - #7100-18OF with overflow holes

LACAVA reserves the right to revise any dimension or information on this sheet without notice. Dimensions are nominal and may vary within an industry accepted tolerance of 1/4". Drawings provided herein are meant to give the user an idea of the product and are not made to scale. Location of plumbing is meant for reference, your specific application may vary. Revised: 9/24/2021



- touch-free safety from spreading undesirable pathogens
- commercial grade automated fixture
- low flow promotes water use savings

